

## Conventional Manual Call Point

MODEL: PS/BG-MS-2

PS/BG-MS-2 is a call point designed to provide a manual alarm interface to any conventional fire alarm control panel. These MCPs are made of MS sheet as per the IS standards. There is a transparent glass protecting the MCP from the front side. A small MS powder coated hammer is attached with the MCP, This is used to break the front glass to generate alarm in the system. All the MCP comes with a factory fitted back box for Surface or Semiflsh mounting on the wall.

### Features:

- **Compatibility with any conventional fire Alarm System**
- **Wall mount facility**
- **Suitable for malls, restaurant, residential etc.**
- **Duel LED on front**
- **Steady RED LED at fire condition**
- **Green LED blinkikng at normal condition (optional)**



### Specification:

Operating voltage	:	<b>24V DC</b>
Current Consumption (Normal/fire)	:	<b>150µA/ 60mA@ 24 VDC</b>
Application Temp range	:	<b>0° C to + 60° C</b>
Humidity	:	<b>5 to 95% Relative Humidity (non condensing)</b>
Housing	:	<b>CRCA Sheet (1.6 mm thick)</b>
Weight	:	<b>475gm</b>
Dimensions (mm)	:	<b>120 x 90 x 55 (W x H x D)</b>
Colour	:	<b>Red</b>

### Operation:

To operate the MCP, break the front glass with attached hammer. Steady glow of Red LED will indicate the activation of MCP. TO reset the MCP open the front cover & change the glass.